

BCSD SERIES "DUAL LOADING" COUNTING SCALE



Example of application with 2 platforms

Counting scale, CONNECTABLE TO A SECOND REMOTE PLATFORM, particularly suitable for taking inventories and for counting small parts. Weight or piece quantity check, weight and pieces' totalisation function, 100 PLU memory.

TECHNICAL FEATURES

- 3 backlit LCD displays with 6 digits 20mm high for simultaneously viewing weight, average piece weight, and number of pieces.
- Membrane waterproof, alphanumeric and functional keypad with 20 keys and acoustic feedback.
- Stainless steel plate, 230x300mm size.
- Level and adjustable feet.
- zero tracking;
- digital calibration;
- auto switch-off;
- backlight command;
- low battery warning.
- Built-in rechargeable battery (about 70h battery life) and 230Vac power adapter.
- RS232/C port for connection to PC or printer.
- Configurable input for connection to second counting platform, with completely programmable capacity and division.
- Packaging: 440x370x220mm size - approximate weight of 5,5kg.

FUNCTIONS

- counting:
 - entry of sampling items,
 - entry of Average Piece Weight,
 - optimisation of the A.P.W.,
 - indication of insufficient A.P.W./sampling quantity,
 - 100 PLU memory, each with: alphanumeric description of 12 characters, tare, A.P.W.;
- weight or piece quantity check, with 2 thresholds and acoustic alarm;
- weight and pieces' totalisation;
- unit of measure conversion: kg, lb;
- zeroing;
- semi-automatic tare or enterable from keypad;

COUNTING FEATURES

Internal sensitivity and minimum recommended A.P.W.:

Model	BCSD6	BCSD15	BCSD30
Internal sensitivity g	0,02	0,05	0,1
Min. recommended A.P.W. g	0,1	0,2	0,5

Dual loading counting scale: Available versions

Code	Max Capacity kg	Standard Division g
BCSD6	6	0,1
BCSD15	15	0,2
BCSD30	30	0,5

NOTE: available connection to a second remote platform.

Dual loading counting scale: Options only available at time of scale's order

Code	Description
OBTPRSH	ABS thermal printer (to be combined with specific cable for each scale). 58 mm paper width; 50 mm roll diameter; power supply through built-in 110-240 Vac power adapter.
RSCBBC	1,5 m cable for connecting ALGM, ASB, ASC, ASG, BCSD and HLD series scales to OBTPRSH printer.
RSCBPCBC	1,5 m cable for connecting ALGM, ASC, BCSD, HLD and KS series scales to PC.