

FPW SERIES PALLET-WEIGHERS



IP67

CE M 3000e

Low profile, easy to move, pallet-weighing scale. Suitable for industrial and commercial applications, in which it's necessary to quickly weigh goods on a pallet. The standard version is provided with approved load cells.

TECHNICAL FEATURES

- Functioning with 4 shear-beam 350Ohm nickel-plated steel load cells, approved according to OIML R60 C3 standards (3000 divisions), IP67 protection degree.
- Moulded sheet-steel structure, oven-fire painted RAL 5007 blue.
- Adjustable, shock-proof jointed feet, level, 2 wheels and handles for moving it.
- Up to 15 Vdc power supply.
- Screened 5m connection cable for connection to the indicator.
- Upon request:
 - 3000e CE-M approval;
 - support column for indicator.

Available versions

Code	Dimensions (LxPxH)	Max Capacity kg	Division g	CE-M Division g
FPW15	1250x840x85	1 500	500	500
FPW30	1250x840x85	3 000	1 000	1 000

Weight Indicators and Accessories

Code	Description
DFWL	Multifunction weight indicator, in IP54 case, with 5-key easy to use keypad.
DFWLI	Multifunction weight indicator, in IP68 stainless steel, with 5-key easy to use keypad.
DFWLKI	Multifunction weight indicator, in IP68 stainless steel, with 17-key easy to use keypad.
AFW	Multifunction weight indicator in ABS, with LCD display having 6 high contrast 24mm digits, power supply through built-in rechargeable battery
ILW	Multifunction weight indicator in ABS, with LCD display having 6 high contrast 52mm digits, power supply through built-in rechargeable battery
CSP42I	STAINLESS steel support column for the DFW, 3590, TRS series' indicators. Easy to install and to clean. Adjustable feet, guaranteeing the maximum stability. Dimensions 520 x 527 x 1026 mm.
CSP38I	STAINLESS steel support column, for the AFW and ILW series' indicators. Easy to install and clean. Adjustable feet, for guaranteeing the maximum stability. Dimensions 520 x 527 x 1026 mm.
CSP38D	STAINLESS steel support column, for the indicators. Easy to install and clean. Column height 750 mm.
CSP38SH	STAINLESS steel support column, for the indicators. Easy to install and clean. Column height 750 mm.
FLATF	Frame for flush floor installation 1000x1000mm
FLMTF	Frame for flush floor installation 1000x1250mm
FLBTF	Frame for flush floor installation 1250x1250mm
FLDTF	Frame for flush floor installation 1250x1500mm
FLETF	Frame for flush floor installation 1500x1500mm