

HLSN "SMART" MOBILE FLOOR SCALES



HLSN with optional remote control



Multi-purpose, easy to use mobile scales. Very practical to move and use, quickening the weighing of any product and in all work environments. The triple automatic reading range allows for the maximum accuracy on the lower weight values.

MAIN FEATURES

- Indicator with waterproof membrane keyboard with 5 function keys, ABS IP54 case..
- Weight indicator with 6 25mm digits on a backlit LCD display, which are clearly visible even in poor lighting conditions.
- Carbon sheet steel bearing structure, oven-fire painted fitted with antishock and adjustable feet, level and wheels.
- Tilttable column attached to the platform with helm and wheels in nylon making it easy to transport.
- Operates with 4 shear-beam load cells able to handle twice the nominal load.
- Accuracy: +/- 0.05% of the capacity.
- Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.
- Power supply through 4 AA batteries, which may also be rechargeable or 12 Vdc power supply with 230 Vac external power adapter
- The operating time is of about 40 hours of continuous use, or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Battery level indication.
- IR input for managing the remote control.

SELECTABLE FUNCTIONS

- X 10 High resolution visualisation.
- Net/Gross or lb/kg conversion.
- Accumulation.
- Formula weighing.
- +/- Checkweighing.
- Percentage weighing.
- Alibi, for approved weight transmission (optional).
- Counting.
- Input/Output.

FUNCTIONS

- Clearing; Automatic and manual tare; enabling selected function; on/off

I/O SECTION

- RS232/C bidirectional port configurable for calibration and configuration from PC.

Available versions

Code	Dimensions (LxPxH)	Max Capacity kg	Standard Division g	CE-M Division g
HLSN	1000 x 1000 x 90	600 / 1500 / 2000	200 / 500 / 1000	-
HLSNM	1000 x 1000 x 90	600 / 1500	-	200 / 500

Options only available at time of order

Code	Description
DFTL10	Infrared remote control, with 18 keys, for use up to 8 m of distance.