

DOT MATRIX TM295 IMPACT PRINTER



Dot matrix impact printer connectable to TRI, TRS03 and 3590M3 series' indicators, designed for the universal printout of delivery notes, labels and tickets. Its compactness and solid structure makes it useful to use in any industrial environment. Furthermore, thanks to its lateral side opening it is possible to use any paper size.

TECHNICAL SPECIFICATIONS

- PRINT METHOD: 7 dot matrix pins
- PRINT RESOLUTION: 16,2 cpi
- FONT: 5 x 7 / 7 x 7
- PRINT SPEED: 2,1 lines/sec.
- COLUMNS: 35 / 42
- PAPER WIDTH: From 80 to 182 mm
- PAPER LENGTH: From 69 to 257 mm
- PRINT WIDTH: From 0.09 to 0.25 mm
- COPY CAPACITY: an original and 2 copies
- INTERFACE: RS232 bidirectional parallel
- DIMENSIONS: 180 X 190.5 X 101.5 mm
- WEIGHT: 1,6 kg
- POWER SUPPLY: fitted with 230 VAC mains adapter
- FITTED CONNECTION CABLE: 1,5 m long

Available versions and accessories

Code	Description
TM295	DOT MATRIX IMPACT PRINTER. 42 col., 60 char/sec., 2.3 lines/sec. Printing of 1 ticket + 2 copies, min. dimensions 80x80 mm. max. 182x270 mm. RS232/C input, 230 vac mains power supply. With 1.5m connection cable.
RSCBLXRS232/C	cable 1.5 m long for connecting the LX300/TM295 printers to the weight indicator.