

"TSCR" TOUCH SCREEN PC



Touch screen PC

Touch screen PC 12" monitor, with adjustable inclination and compact size. Ideal in applications which require a simple, immediate and easily visible operator interface, with dedicated keys and easy recall of the main functions. The IP64 protection from dust and external agents allows to use it also in industrial applications.

MAIN FEATURES

- Adjustable 12" monitor with a very bright, resistive touch screen having a visual angle of 160/160.
- 1024 x 768 maximum resolution.
- ABS and black aluminium case, fitted with a LED front for ON/OFF indication.
- IP64 protection.
- Maximum operating temperature: 0 ÷ 50°C.
- Dimensions: 304 x 210 x 275 mm (LxHxP).
- Weight: 1,8 kg.
- Power supply with external 110/240 Vac power adapter.

I/O SECTION

- 2 RS232 configurable ports for connection to printer/labeller.
- 2 USB 2.0 ports.
- 2 LAN ports which allow to connect to any display or other necessary peripheral units for managing the application.

Available versions

Code	Description
------	-------------

TSCR03	Touch Screen PC , connectable with a DFW or DGT series' weight indicator, in the weigh bridge management version. Fitted with the "Weitruk" software and the functioning Alibi Memory (to be installed in the indicator). TFT 12" monitor with adjustable inclination, 1024 x 768 maximum resolution, easily visible from all angles.
--------	---

Options available only at time of order

Code	Description
------	-------------

BADGER	Reader of magnetic Badges with USB data output for connection to PC, for automatic enabling of the weigh data.
BADGE10	Set of 10 magnetic Cards for use with BADGER option.
CHIPR	Reader of CHIP CARDS with USB output data for connection to PC, for automatic enabling of the weigh data.
CHIP10	Set of 10 Chip Cards for use with CHIPR option.